

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-1050 Schwarz

|             |                |                                 |
|-------------|----------------|---------------------------------|
| Version     | Revision Date: | Date of last issue: 30.09.2019  |
| 1.1 GB / EN | 23.07.2021     | Date of first issue: 30.09.2019 |

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Carsystem KS-1050 Schwarz / Black  
Product code : 126.023

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Corrosion inhibitor  
Recommended restrictions on use : professional use, Industrial use

#### 1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH  
Esinger Steinweg 50  
25436 Uetersen  
Germany  
info@vosschemie.de  
Telephone : 04122 717 0  
Telefax : 04122 717158  
**Responsible Department** : Laboratory  
04122 717 0  
sds@vosschemie.de

#### 1.4 Emergency telephone number

Telephone : POISONS INFORMATION CENTRE  
Australia  
13 11 26

#### 1.5 Details of the supplier/importer

Company : Sydney Automotive Paints and Equipment  
Unit A3, 366 Edgar Street  
Condell Park, 2200  
reception@sape.com.au  
Telephone : 02 9772 9000  
Telefax : 02 9772 9001  
**Responsible Department** : Marketing  
02 9772 9000

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-1050 schwarz

Version  
1.1

GB / EN

Revision Date:  
23.07.2021

Date of last issue: 30.09.2019  
Date of first issue: 30.09.2019

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|  |   |
|--|---|
| Aerosols, Category 1   | H222: Extremely flammable aerosol.<br>H229: Pressurised container: May burst if heated. |
| Skin irritation, Category 2  | H315: Causes skin irritation.   |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness.  |
| Long-term (chronic) aquatic hazard, Category 2                                       | H411: Toxic to aquatic life with long lasting effects.                                  |

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :  
H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : Buildup of explosive mixtures possible without sufficient ventilation.

Precautionary statements :  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

##### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe spray.

##### Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-1050 schwarz

Version  
1.1

GB / EN

Revision Date:  
23.07.2021

Date of last issue: 30.09.2019  
Date of first issue: 30.09.2019

### Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

### Hazardous components which must be listed on the label:

cyclohexane  
Hydrocarbons, C6, isoalkanes, <5% hexane  
butanone  
Hydrocarbons, C9, Aromatics

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : aerosol  
Mixture

#### Components

| Chemical name | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number     | Classification  | Concentration<br>(% w/w) |
|---------------|---|---|--------------------------|
| cyclohexane   | 110-82-7<br>203-806-2<br>601-017-00-1<br>01-2119463273-41 | Flam. Liq. 2; H225<br>Skin Irrit. 2; H315<br>STOT SE 3; H336<br>(Central nervous system)<br>Asp. Tox. 1; H304<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410<br><br>M-Factor (Acute aquatic toxicity): 1<br>M-Factor (Chronic aquatic toxicity): 1 | >= 12.5 - < 20           |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-1050 schwarz

Version  
1.1

GB / EN

Revision Date:  
23.07.2021

Date of last issue: 30.09.2019  
Date of first issue: 30.09.2019

|   |  |  |                |
|---|--|--|----------------|
| Hydrocarbons, C6, isoalkanes,<br><5% hexane | 64742-49-0<br>931-254-9<br>01-2119484651-34              | Flam. Liq. 2; H225<br>Skin Irrit. 2; H315<br>STOT SE 3; H336<br>(Central nervous<br>system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 2;<br>H411                               | >= 10 - < 12.5 |
| butanone                                    | 78-93-3<br>201-159-0<br>606-002-00-3<br>01-2119457290-43 | Flam. Liq. 2; H225<br>Eye Irrit. 2; H319<br>STOT SE 3; H336<br>(Central nervous<br>system)<br>EUH066   | >= 5 - < 10    |
| Hydrocarbons, C9, Aromatics                 | Not Assigned<br>918-668-5<br>01-2119455851-35            | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous<br>system)<br>STOT SE 3; H335<br>(Respiratory system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 2;<br>H411<br>EUH066 | >= 5 - < 10    |

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : First aider needs to protect himself.  
Remove from exposure, lie down.  
If unconscious, place in recovery position and seek medical advice.  
Take off contaminated clothing and shoes immediately.
- If inhaled : Move to fresh air.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
If eye irritation persists, consult a specialist.
- If swallowed : Swallowing is not regarded as a possible method for exposure.  
Immediately give large quantities of water to drink.  
Get medical attention immediately.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-1050 schwarz

|             |                |                                 |
|-------------|----------------|---------------------------------|
| Version     | Revision Date: | Date of last issue: 30.09.2019  |
| 1.1 GB / EN | 23.07.2021     | Date of first issue: 30.09.2019 |

---

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.  
May cause drowsiness or dizziness.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

Hazchem: 2YE

### 5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
Dry powder  
Water spray jet  
Alcohol-resistant foam

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Vapours may form explosive mixtures with air.  
Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

Hazardous combustion products : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment. Wear suitable respiratory protection equipment.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Use water spray to cool unopened containers.  
In the event of fire and/or explosion do not breathe fumes.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.  
Evacuate personnel to safe areas.  
Remove all sources of ignition.  
Ensure adequate ventilation.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-1050 schwarz

|             |                |                                 |
|-------------|----------------|---------------------------------|
| Version     | Revision Date: | Date of last issue: 30.09.2019  |
| 1.1 GB / EN | 23.07.2021     | Date of first issue: 30.09.2019 |

---

Avoid inhalation of vapour or mist.  
Avoid contact with skin, eyes and clothing.

### 6.2 Environmental precautions

Environmental precautions : Should not be released into the environment.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ventilate the area.  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Local/Total ventilation : Ensure adequate ventilation.

Advice on safe handling : Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C / 122 °F. Also after use, do not open with force or burn.  
Provide sufficient air exchange and/or exhaust in work rooms.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Keep away from open flames, hot surfaces and sources of ignition. Keep away from direct sunlight.

Hygiene measures : Do not inhale aerosol.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Please observe the storage instructions for aerosols! Keep containers tightly closed in a cool, well-ventilated place. Solvent vapours are heavier than air and may spread along floors. Keep away from direct sunlight. Keep away from heat and sources of ignition.

Further information on storage conditions : Storage must be in accordance with the BetrSichV (Germany).

Advice on common storage : Keep away from food and drink.

### 7.3 Specific end use(s)

Specific use(s) : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-1050 schwarz

Version  
1.1

GB / EN

Revision Date:  
23.07.2021

Date of last issue: 30.09.2019  
Date of first issue: 30.09.2019

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

| Components  | CAS-No.  | Value type (Form of exposure)  | Control parameters                 | Basis      |
|---|----------|--|------------------------------------|------------|
| cyclohexane                                       | 110-82-7 | TWA  | 200 ppm<br>700 mg/m <sup>3</sup>   | 2006/15/EC |
|   |          | Further information: Indicative  |                                    |            |
|   |          | TWA  | 100 ppm<br>350 mg/m <sup>3</sup>   | GB EH40    |
|   |          | STEL   | 300 ppm<br>1,050 mg/m <sup>3</sup> | GB EH40    |
| butane (containing < 0,1 % butadiene (203-450-8)) | 106-97-8 | STEL   | 750 ppm<br>1,810 mg/m <sup>3</sup> | GB EH40    |
|   |          | Further information: Capable of causing cancer and/or heritable genetic damage.  |                                    |            |
|   |          | TWA  | 600 ppm<br>1,450 mg/m <sup>3</sup> | GB EH40    |
|   |          | Further information: Capable of causing cancer and/or heritable genetic damage.  |                                    |            |
| butanone  | 78-93-3  | TWA  | 200 ppm<br>600 mg/m <sup>3</sup>   | 2000/39/EC |
|   |          | Further information: Indicative  |                                    |            |
|   |          | STEL   | 300 ppm<br>900 mg/m <sup>3</sup>   | 2000/39/EC |
|   |          | Further information: Indicative  |                                    |            |
|   |          | TWA  | 200 ppm<br>600 mg/m <sup>3</sup>   | GB EH40    |
|   |          | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                                    |            |
|   |          | STEL   | 300 ppm<br>899 mg/m <sup>3</sup>   | GB EH40    |
|   |          | Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. |                                    |            |

##### Biological occupational exposure limits

| Substance name | CAS-No. | Control parameters                         | Sampling time | Basis          |
|----------------|---------|--|---------------|----------------|
| butanone       | 78-93-3 | butan-2-one: 70 micromol per litre (Urine) | After shift   | GB EH40<br>BAT |

##### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects                            | Value                 |
|----------------|---------|-----------------|---|-----------------------|
| cyclohexane    | Workers | Inhalation      | Long-term systemic effects, Long-term local effects | 700 mg/m <sup>3</sup> |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-1050 schwarz

Version  
1.1

GB / EN

Revision Date:  
23.07.2021

Date of last issue: 30.09.2019  
Date of first issue: 30.09.2019

|  |           |              |   |                        |
|--|-----------|--------------|---|------------------------|
|  | Workers   | Inhalation   | Acute systemic effects, Acute local effects         | 1400 mg/m <sup>3</sup> |
|  | Workers   | Skin contact | Long-term systemic effects                          | 2016 mg/kg             |
|  | Consumers | Inhalation   | Long-term systemic effects, Long-term local effects | 206 mg/m <sup>3</sup>  |
|  | Consumers | Inhalation   | Acute systemic effects, Acute local effects         | 412 mg/m <sup>3</sup>  |
|  | Consumers | Skin contact | Long-term systemic effects                          | 1186 mg/kg             |
|  | Consumers | Oral         | Long-term systemic effects                          | 59.4 mg/kg             |
| Hydrocarbons, C6, isoalkanes, <5% hexane | Workers   | Inhalation   | Long-term systemic effects                          | 5306 mg/m <sup>3</sup> |
|  | Workers   | Skin contact | Long-term systemic effects                          | 13964 mg/kg            |
|  | Consumers | Inhalation   | Long-term systemic effects                          | 1131 mg/m <sup>3</sup> |
|  | Consumers | Skin contact | Long-term systemic effects                          | 1377 mg/kg             |
|  | Consumers | Oral         | Long-term systemic effects                          | 1301 mg/kg             |
| butanone                                 | Workers   | Inhalation   | Long-term systemic effects                          | 600 mg/m <sup>3</sup>  |
|  | Workers   | Skin contact | Long-term systemic effects                          | 1161 mg/kg             |
|  | Consumers | Inhalation   | Long-term systemic effects                          | 106 mg/m <sup>3</sup>  |
|  | Consumers | Skin contact | Long-term systemic effects                          | 412 mg/kg              |
|  | Consumers | Oral         | Long-term systemic effects                          | 31 mg/kg               |

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value        |
|----------------|---------------------------|--------------|
| cyclohexane    | Fresh water               | 0.207 mg/l   |
|                | Marine water              | 0.207 mg/l   |
|                | Sewage treatment plant    | 3.24 mg/l    |
|                | Fresh water sediment      | 16.68 mg/kg  |
|                | Marine sediment           | 16.68 mg/kg  |
|                | Soil                      | 3.38 mg/kg   |
| butanone       | Fresh water               | 55.8 mg/l    |
|                | Marine water              | 55.8 mg/l    |
|                | Sewage treatment plant    | 709 mg/l     |
|                | Fresh water sediment      | 284.74 mg/kg |
|                | Marine sediment           | 284.7 mg/kg  |
|                | Soil                      | 22.5 mg/kg   |



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-1050 schwarz

Version 1.1 GB / EN Revision Date: 23.07.2021 Date of last issue: 30.09.2019  
Date of first issue: 30.09.2019

---

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Tightly fitting safety goggles  
Safety glasses with side-shields conforming to EN166

#### Hand protection

Material : butyl-rubber  
Break through time : > 480 min  
Glove thickness : >= 0.4 mm  
Directive : DIN EN 374  
Protective index : Class 6

Remarks : The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this has to be observed. Preventive skin protection

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.  
Long sleeved clothing

Respiratory protection : No personal respiratory protective equipment normally required.  
In case of inadequate ventilation wear respiratory protection.  
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Filter type : Filter type A-P

Protective measures : Use only with adequate ventilation.  
When using do not eat, drink or smoke.  
Avoid contact with skin, eyes and clothing.  
Do not breathe vapours or spray mist.

#### Environmental exposure controls

Soil : Avoid subsoil penetration.  
Water : Do not flush into surface water or sanitary sewer system.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : aerosol  
Colour : black  
Odour : solvent-like  
Melting point/freezing point : not determined  
Initial boiling point and boiling : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-1050 schwarz

|             |                |                                 |
|-------------|----------------|---------------------------------|
| Version     | Revision Date: | Date of last issue: 30.09.2019  |
| 1.1 GB / EN | 23.07.2021     | Date of first issue: 30.09.2019 |

---

range

Upper explosion limit / Upper flammability limit : 10.9 %(V)

Lower explosion limit / Lower flammability limit : 1.1 %(V)

Flash point : < 0 °C

Ignition temperature : > 200 °C

pH : not determined substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : not determined

Viscosity, kinematic : not determined

Solubility(ies)

Water solubility : immiscible

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 3,500 hPa (20 °C)

Density : 0.83 g/cm<sup>3</sup> (20 °C)

### 9.2 Other information

Explosives : Not explosive  
In use, may form flammable/explosive vapour-air mixture.

Self-ignition : not auto-flammable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if used as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Keep away from heat and sources of ignition.  
Strong sunlight for prolonged periods.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-1050 schwarz

Version 1.1 GB / EN Revision Date: 23.07.2021 Date of last issue: 30.09.2019  
Date of first issue: 30.09.2019

---

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **cyclohexane:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 32.88 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg  
Method: OECD Test Guideline 402

##### **Hydrocarbons, C6, isoalkanes, <5% hexane:**

Acute oral toxicity : LD50 Oral (Rat): 16,750 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 259.4 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 3,350 mg/kg  
Method: OECD Test Guideline 402

##### **butanone:**

Acute oral toxicity : LD50 Oral (Rat): 3,460 mg/kg  
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,000 mg/kg  
Method: OECD Test Guideline 402

##### **Hydrocarbons, C9, Aromatics:**

Acute oral toxicity : LD50 Oral (Rat, female): ca. 3,492 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.193 mg/l  
Exposure time: 4 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-1050 schwarz

|         |                |                                 |
|---------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 30.09.2019  |
| 1.1     | 23.07.2021     | Date of first issue: 30.09.2019 |

Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 3,160 mg/kg  
Method: OECD Test Guideline 402

### **Skin corrosion/irritation**

Causes skin irritation.

#### **Components:**

##### **Hydrocarbons, C6, isoalkanes, <5% hexane:**

Result : Skin irritation

##### **Hydrocarbons, C9, Aromatics:**

Result : Repeated exposure may cause skin dryness or cracking.

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Components:**

##### **Hydrocarbons, C6, isoalkanes, <5% hexane:**

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

##### **Hydrocarbons, C9, Aromatics:**

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### **Carcinogenicity**

Not classified based on available information.

#### **Components:**

##### **Hydrocarbons, C6, isoalkanes, <5% hexane:**

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-1050 schwarz

|             |                |                                 |
|-------------|----------------|---------------------------------|
| Version     | Revision Date: | Date of last issue: 30.09.2019  |
| 1.1 GB / EN | 23.07.2021     | Date of first issue: 30.09.2019 |

---

### Hydrocarbons, C9, Aromatics:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

May cause drowsiness or dizziness.

### Components:

#### Hydrocarbons, C6, isoalkanes, <5% hexane:

Assessment : May cause drowsiness or dizziness.

### Hydrocarbons, C9, Aromatics:

Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

### STOT - repeated exposure

Not classified based on available information.

### Aspiration toxicity

Not classified based on available information.

### Components:

#### Hydrocarbons, C6, isoalkanes, <5% hexane:

May be fatal if swallowed and enters airways.

### Hydrocarbons, C9, Aromatics:

May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

cyclohexane:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-1050 schwarz

Version 1.1 GB / EN Revision Date: 23.07.2021 Date of last issue: 30.09.2019  
Date of first issue: 30.09.2019

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 4.53 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.9 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): 9.317 mg/l  
End point: Growth rate  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- M-Factor (Acute aquatic toxicity) : 1
- M-Factor (Chronic aquatic toxicity) : 1

### Hydrocarbons, C6, isoalkanes, <5% hexane:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 18.27 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 31.9 mg/l  
Exposure time: 48 h
- Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (algae)): 3.034 mg/l  
Exposure time: 72 h
- Toxicity to fish (Chronic toxicity) : NOELR: 4.089 mg/l  
Exposure time: 28 d  
Species: Oncorhynchus mykiss (rainbow trout)
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 7.138 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)

### Ecotoxicology Assessment

- Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### butanone:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l  
End point: mortality  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 308 mg/l  
End point: Immobilization  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): 1,972

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-1050 schwarz

|         |                |                                 |
|---------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 30.09.2019  |
| 1.1     | 23.07.2021     | Date of first issue: 30.09.2019 |

plants  
mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

### Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

### Hydrocarbons, C9, Aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 9.2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3.2 mg/l  
End point: Immobilization  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): 1 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR: 1.228 mg/l  
Exposure time: 28 d  
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 2.144 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)

## 12.2 Persistence and degradability

### Components:

#### **cyclohexane:**

Biodegradability : Biodegradation: 77 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

#### **Hydrocarbons, C6, isoalkanes, <5% hexane:**

Biodegradability : Biodegradation: 81 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

#### **Hydrocarbons, C9, Aromatics:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 78 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-1050 schwarz

Version 1.1 GB / EN Revision Date: 23.07.2021 Date of last issue: 30.09.2019  
Date of first issue: 30.09.2019

---

### 12.3 Bioaccumulative potential

#### Components:

##### **cyclohexane:**

Bioaccumulation : Bioconcentration factor (BCF): 167

Partition coefficient: n-octanol/water : log Pow: 3.44 (20 °C)

##### **Hydrocarbons, C6, isoalkanes, <5% hexane:**

Partition coefficient: n-octanol/water : log Pow: 3.6 (20 °C)

##### **butanone:**

Partition coefficient: n-octanol/water : log Pow: 0.3 (40 °C)  
pH: 7

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
Dispose of in conjunction with appropriate waste disposal



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-1050 schwarz

|             |                |                                 |
|-------------|----------------|---------------------------------|
| Version     | Revision Date: | Date of last issue: 30.09.2019  |
| 1.1 GB / EN | 23.07.2021     | Date of first issue: 30.09.2019 |

---

authorities and in accordance with disposal regulations.

Contaminated packaging : Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:  
08 01 11, waste paint and varnish containing organic solvents  
or other hazardous substances  
15 01 10, packaging containing residues of or contaminated  
by hazardous substances

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

|      |           |
|------|-----------|
| ADN  | : UN 1950 |
| ADR  | : UN 1950 |
| RID  | : UN 1950 |
| IMDG | : UN 1950 |
| IATA | : UN 1950 |

#### 14.2 UN proper shipping name

|      |                               |
|------|-------------------------------|
| ADN  | : AEROSOLS                    |
| ADR  | : AEROSOLS                    |
| RID  | : AEROSOLS                    |
| IMDG | : AEROSOLS<br>(CYCLOHEXANE, ) |
| IATA | : Aerosols, flammable         |

#### 14.3 Transport hazard class(es)

|      |       |
|------|-------|
| ADN  | : 2   |
| ADR  | : 2   |
| RID  | : 2   |
| IMDG | : 2.1 |
| IATA | : 2.1 |

#### 14.4 Packing group

|                         |                              |
|-------------------------|------------------------------|
| <b>ADN</b>              |                              |
| Packing group           | : Not assigned by regulation |
| Classification Code     | : 5F                         |
| Labels                  | : 2.1                        |
| <b>ADR</b>              |                              |
| Packing group           | : Not assigned by regulation |
| Classification Code     | : 5F                         |
| Labels                  | : 2.1                        |
| Tunnel restriction code | : (D)                        |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-1050 schwarz

|             |                |                                 |
|-------------|----------------|---------------------------------|
| Version     | Revision Date: | Date of last issue: 30.09.2019  |
| 1.1 GB / EN | 23.07.2021     | Date of first issue: 30.09.2019 |

---

### RID

Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

### IMDG

Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

### IATA (Cargo)

Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Division 2.1 - Flammable gases

### IATA (Passenger)

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Division 2.1 - Flammable gases

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : yes

### ADR

Environmentally hazardous : yes

### RID

Environmentally hazardous : yes

### IMDG

Marine pollutant : yes

**Hazchem: 2YE**

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: cyclohexane (Number on list 57)

REACH - Candidate List of Substances of Very High : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-1050 schwarz

|             |                |                                 |
|-------------|----------------|---------------------------------|
| Version     | Revision Date: | Date of last issue:             |
| 1.1 GB / EN | 23.07.2021     | 30.09.2019                      |
|             |                | Date of first issue: 30.09.2019 |

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P3a FLAMMABLE AEROSOLS

E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Directive 2004/42/EC  
Volatile organic compounds (VOC) content: < 840 g/l  
VOC content for the product in a ready to use condition.

### 15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

## SECTION 16: Other information

### Full text of H-Statements

H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.  
H315 : Causes skin irritation.  
H319 : Causes serious eye irritation.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Skin Irrit. : Skin irritation  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-1050 schwarz

|             |                |                                 |
|-------------|----------------|---------------------------------|
| Version     | Revision Date: | Date of last issue: 30.09.2019  |
| 1.1 GB / EN | 23.07.2021     | Date of first issue: 30.09.2019 |

|                   |  |
|-------------------|--|
| 2006/15/EC        | : Europe. Indicative occupational exposure limit values  |
| GB EH40           | : UK. EH40 WEL - Workplace Exposure Limits               |
| GB EH40 BAT       | : UK. Biological monitoring guidance values              |
| 2000/39/EC / TWA  | : Limit Value - eight hours                              |
| 2000/39/EC / STEL | : Short term exposure limit                              |
| 2006/15/EC / TWA  | : Limit Value - eight hours                              |
| GB EH40 / TWA     | : Long-term exposure limit (8-hour TWA reference period) |
| GB EH40 / STEL    | : Short-term exposure limit (15-minute reference period) |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

|                   |            |
|-------------------|------------|
| Aerosol 1         | H222, H229 |
| Skin Irrit. 2     | H315       |
| STOT SE 3         | H336       |
| Aquatic Chronic 2 | H411       |

#### Classification procedure:

|                    |
|--------------------|
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-1050 schwarz

Version

1.1

GB / EN

Revision Date:

23.07.2021

Date of last issue: 30.09.2019

Date of first issue: 30.09.2019

---

to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.