



## Pneumatic-hydraulic blind riveting tool

- the **high setting force** enables safe processing of quenched and tempered carbon steel blind rivets
- **innovative buffer system** for damping the tear-off impacts
- **Switchable rivet suction** for vertical riveting applications
- **innovative, active control** of the feeding mechanism increases the Tool life and maintenance times of the chuck jaws by a multiple
- Option between compressed air connection to the rear or right side
- automatic overpressure safety valve
- extendable suspension bracket, **ergonomically designed Handle** with vibration-damping rubber pad
- **automatic air-driven mandrel ejection** into the removable collection container at the rear.



Extension unit 50 mm  
 (total length 106 mm)  
 Art.-No. 578113



Extension unit 100-mm  
 (total length 156 mm)  
 Art.-No. 578114

Art.-No. 571110

## for ultra high-strength blind rivets up to 1,600N/mm<sup>2</sup>



**Scope of delivery:**

- 1 x riveting pliers
- 1 x hydraulic oil 100ml
- 1 x carrying case

**Technical data:**

- |                     |  |
|---------------------|--|
| weight:             | 2,0 kg   |
| Operating pressure: | 5-7 bar  |
| Hose connection:    | 6 mm Ø (1/4")  |
| Air consumption:    | approx. 4.8 l per rivet  |
| Setting force:      | 23,000 N   |
| Working range:      | Blind rivets up to<br>Ø 6,5 mm - all materials<br>Ø 8,0 mm - Aluminium |

capacity -  
 Collection container: approx. 100 - 200 pieces

