



Auto Refinishing Products

Page 1/15

Printing date: 14.03.2022

Revision date: 14.03.2022

Version no. 1

Safety Data Sheet
according to WHS Regulations

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

· Product identifier

· **Trade name:** **BODY 770 ANTISIL SPRAY**

· **Article number:** 881

· **Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Process category** PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

· **Environmental release category** ERC2 Formulation into mixture

· **Article category** AC1 Vehicles

· **Application of the substance / the mixture**

All-purpose cleaner

Surface protection

· Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

· **Further information obtainable from:**

Sydney Automotive Paints & Equipment PTY LTD

Unit A3, 366 Edgar St. Condell Park NSW 2200

AUSTRALIA, Tel. +02 9772 9000 , +02 9772 9001

· **Emergency telephone number:**

If poisoning occurs contact a doctor or Poisons Information Centre. Phone Australia 131 126, New Zeland 0800 764 766.

AU

Continue on page 2

Trade name: **BODY 770 ANTISIL SPRAY**

* **2 Hazard(s) Identification**

· Classification of the substance or mixture



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.



health hazard

Muta. 1A H340 May cause genetic defects.
Carc. 1A H350 May cause cancer.
STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.

· Label elements

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02



GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

butane, pure
Low boiling point hydrogen treated naphtha
isobutane

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.
H340 May cause genetic defects.
H350 May cause cancer.
H372 Causes damage to the central nervous system through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards**

· **Results of PBT and vPvB assessment**














· **PBT:** Not applicable.
· **vPvB:** Not applicable.

* **3 Composition and Information on Ingredients**

· Chemical characterisation: Mixtures

· **Description:** Mixture of hazardous substances listed below with nonhazardous additions.

Trade name: BODY 770 ANTISIL SPRAY**Dangerous components:**

| | | |
|----------------------------|--|---------|
| CAS: 64742-82-1 | Low boiling point hydrogen treated naphtha | 45-<50% |
| EINECS: 265-185-4 |  Flam. Liq. 3, H226 | |
| Index number: 649-330-00-2 |  STOT RE 1, H372; Asp. Tox. 1, H304 | |
| CAS: 106-97-8 | butane, pure | 30-<35% |
| EINECS: 203-448-7 |  Flam. Gas 1, H220 | |
| Index number: 601-004-00-0 |  Press. Gas C, H280 | |
| RTECS: EJ 4200000 |  Acute Tox. 3, H331 | |
| |  Muta. 1A, H340; Carc. 1A, H350 | |
| CAS: 64742-49-0 | Naphtha (petroleum), hydrotreated light | 10-<15% |
| EINECS: 265-151-9 |  Flam. Liq. 2, H225 | |
| Index number: 649-328-00-1 |  Asp. Tox. 1, H304 | |
| CAS: 75-28-5 | isobutane | 1-<5% |
| EINECS: 200-857-2 |  Flam. Gas 1, H220 | |
| Index number: 601-004-00-0 |  Press. Gas C, H280 | |
| RTECS: TZ 4300000 |  Muta. 1A, H340; Carc. 1A, H350 | |
| CAS: 74-98-6 | propane | 1-<5% |
| EINECS: 200-827-9 |  Flam. Gas 1, H220 | |
| Index number: 601-003-00-5 |  Press. Gas C, H280 | |
| RTECS: TX 2275000 | | |

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures**Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

Information for doctor:

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures**Extinguishing media**

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.

Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

Speial protective equipment and fire fighting procedures: Mouth respiratory protective device.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental Release Measures**Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Trade name: BODY 770 ANTISIL SPRAY

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* **7 Handling and Storage**

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

* **8 Exposure controls and personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**

 - 106-97-8 butane, pure
WES Long-term value: 1900 mg/m³, 800 ppm
 - 74-98-6 propane
WES Asphyxiant
- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Trade name: **BODY 770 ANTISIL SPRAY**

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:** Fluorocarbon rubber (Viton)

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Rubber gloves

· **Eye protection:**

Safety glasses



Tightly sealed goggles

· **Body protection:** Protective work clothing

* **9 Physical and Chemical Properties**

· Information on basic physical and chemical properties

· **General Information**

· **Appearance:**

| | |
|---------------------------|-----------------|
| · Form: | Gaseous |
| · Colour: | Colourless |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |
| · pH-value: | Not determined. |

· **Change in condition**

| | |
|---|---------------|
| · Melting point/freezing point: | Undetermined. |
| · Initial boiling point and boiling range: | -44,5 °C |

| | |
|-------------------------------------|--|
| · Flash point: | < 0 °C |
| · Flammability (solid, gas): | Not applicable. |
| · Autoignition temperature: | 296 °C |
| · Decomposition temperature: | Not determined. |
| · Auto-ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Risk of explosion by shock, friction, fire or other sources of ignition. |
| · Explosion limits: | |
| · Lower: | 1.5 Vol % |

Trade name: **BODY 770 ANTISIL SPRAY**

| | |
|--|--|
| Upper: | 8.5 Vol % |
| · Vapour pressure at 20 °C: | 2,100 hPa |
| · Density at 20 °C: | 0.49019 g/cm ³ |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not applicable. |
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 49.3 % |
| VOC (EC) | 490.2 g/l |
| Solids content (volume): | 0.0 % |
| · Other information | No further relevant information available. |

10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

* 11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity**
- **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h 2.018 mg/l (rat)

106-97-8 butane, pure

Inhalative LC50/4 h 658 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Continue on page 7

AU

Trade name: **BODY 770 ANTISIL SPRAY**

· **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**

Muta. 1A, Carc. 1A

* **12 Ecological Information**

· **Toxicity**

· **Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· **Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly.

Do not just throw it away

· **Behaviour in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

· **vPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

* **14 Transport information**

· **UN-Number**

· **ADG, IMDG, IATA**

UN1950

· **UN proper shipping name**

· **ADG**

UN1950 AEROSOLS

· **IMDG**

AEROSOLS (TURPENTINE SUBSTITUTE, Naphtha (petroleum), hydrotreated light), MARINE POLLUTANT

· **IATA**

AEROSOLS, flammable

Continue on page 8
AU

Trade name: **BODY 770 ANTISIL SPRAY**

· Transport hazard class(es)

· **ADG**



· **Class** 2.5F Gases.
· **Label** 2.1

· **IMDG**



· **Class** 2.1 Gases.
· **Label** 2.1

· **IATA**



· **Class** 2.1 Gases.
· **Label** 2.1

· Packing group

· **ADG, IMDG, IATA**

· Environmental hazards:

· **Marine pollutant:**

· Special precautions for user

· **Hazard identification number (Kemler code):**

· **EMS Number:**

· **Stowage Code**

· **Segregation Code**

Void

Product contains environmentally hazardous substances: Low boiling point hydrogen treated naphtha

Yes

Symbol (fish and tree)

Warning: Gases.

-

F-D,S-U

SW1 Protected from sources of heat.

SW2 Clear of living quarters.

SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

· Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

· **ADG**

· **Limited quantities (LQ)**

· **Excepted quantities (EQ)**

1L

Code: E0

Not permitted as Excepted Quantity

Trade name: **BODY 770 ANTISIL SPRAY**

| | |
|-----------------------------------|--|
| · Transport category | 2 |
| · Tunnel restriction code | D |
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E0 Not permitted as Excepted Quantity |
| · UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 |

* **15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

· **Australian Inventory of Industrial Chemicals**

All ingredients are listed.

· **Standard for the Uniform Scheduling of Medicines and Poisons**

None of the ingredients is listed.

· **Australia: Priority Existing Chemicals**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

butane, pure
Low boiling point hydrogen treated naphtha
isobutane

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.
H340 May cause genetic defects.
H350 May cause cancer.
H372 Causes damage to the central nervous system through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** P3a FLAMMABLE AEROSOLS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

Trade name: BODY 770 ANTISIL SPRAY**· National regulations:****· Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has been carried out.*** 16 Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H331 Toxic if inhaled.

H340 May cause genetic defects.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

· Department issuing SDS: Department of Quality Control**· Contact:**

HB BODY S.A

Ms Olympia Stamkou

Ph: +30 2310 790 032

fax: +30 2310 790 033

email: stamkou@hbbody.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity – Category 3

Muta. 1A: Germ cell mutagenicity – Category 1A

Carc. 1A: Carcinogenicity – Category 1A

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

· * Data compared to the previous version altered.

Trade name: BODY 770 ANTISIL SPRAY**Annex: Exposure scenario 1****· Short title of the exposure scenario****· Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites**· Product category** PC9a Coatings and paints, thinners, paint removers**· Process category** PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities**· Article category** AC1 Vehicles**· Environmental release category** ERC2 Formulation into mixture**· Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· Conditions of use According to directions for use.**· Duration and frequency**

5 workdays/week.

Frequency of use:

· Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· Physical state Aerosol**· Concentration of the substance in the mixture** The substance is main component.**· Other operational conditions****· Other operational conditions affecting environmental exposure** Use only on hard ground.**· Other operational conditions affecting worker exposure**

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid contact with the skin.

· Other operational conditions affecting consumer exposure Keep out of the reach of children.**· Other operational conditions affecting consumer exposure during the use of the product** Not applicable.**· Risk management measures****· Worker protection****· Organisational protective measures**

No special measures required.

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Provide explosion-proof electrical equipment.

Use product only in enclosed systems.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the skin.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Measures for consumer protection

Ensure adequate labelling.

Keep locked up and out of the reach of children.

Observe consumer information and advice on safe use.

· Environmental protection measures**· Water**

Do not allow to reach sewage system.

Trade name: BODY 770 ANTISIL SPRAY

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

· Soil

Prevent contamination of soil.

The product is only processed over the concrete collecting basin.

· Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

· Disposal procedures Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste type Partially emptied and uncleaned packaging

· Exposure estimation**· Consumer**

Not relevant for this Exposure Scenario.

This product is to be used by professional technicians only.

· Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

AU

Continue on page 13

Trade name: BODY 770 ANTISIL SPRAY**Annex: Exposure scenario 2****· Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· Conditions of use According to directions for use.**· Duration and frequency** Frequency of use:**· Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· Physical state Fluid**· Concentration of the substance in the mixture** Raw material.**· Other operational conditions****· Other operational conditions affecting environmental exposure**

No special measures required.

Use only on hard ground.

· Other operational conditions affecting worker exposure

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· Other operational conditions affecting consumer exposure No special measures required.**· Other operational conditions affecting consumer exposure during the use of the product** Not applicable.**· Risk management measures****· Worker protection****· Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Use product only in enclosed systems.

· Personal protective measures Do not inhale gases / fumes / aerosols.**· Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· Environmental protection measures**· Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

· Soil

The product is only processed over the concrete collecting basin.

Prevent contamination of soil.

· Disposal measures Ensure that waste is collected and contained.**· Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.**· Waste type** Partially emptied and uncleaned packaging**· Exposure estimation****· Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

· Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

Trade name: BODY 770 ANTISIL SPRAY**Annex: Exposure scenario 3****· Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· Conditions of use According to directions for use.**· Duration and frequency** Frequency of use:**· Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· Physical state Fluid**· Concentration of the substance in the mixture** Raw material.**· Other operational conditions****· Other operational conditions affecting environmental exposure**

No special measures required.

Use only on hard ground.

· Other operational conditions affecting worker exposure

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid contact with the skin.

· Other operational conditions affecting consumer exposure No special measures required.**· Other operational conditions affecting consumer exposure during the use of the product** Not applicable.**· Risk management measures****· Worker protection****· Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Use product only in enclosed systems.

· Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· Environmental protection measures**· Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

· Soil

The product is only processed over the concrete collecting basin.

Prevent contamination of soil.

· Disposal measures Ensure that waste is collected and contained.**· Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.**· Waste type** Partially emptied and uncleaned packaging

Continue on page 15

AU

Trade name: BODY 770 ANTISIL SPRAY

· **Exposure estimation**

· **Consumer**

This product is to be used by professional technicians only.
Not relevant for this Exposure Scenario.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.